



LH13QBREBGXZA
Premium display QBR series

Specification

- **Display**
 - **Diagonal Size**13"
 - **Panel Type**ADS
 - **Resolution**1,920 x 1,080
 - **Pixel Pitch (HxV)**0.153 (H) x 0.153 (V)
 - **Brightness**300
 - **Contrast Ratio**800:1
 - **Viewing Angle (H/V)**178/178
 - **Response Time**8ms
 - **Color Gamut**45%
 - **Glass Haze**25%
 - **H-Scanning Frequency**30~81kHz
 - **Maximum Pixel Frequency**594MHz
 - **V-Scanning Frequency**48~75Hz
 - **Dynamic Contrast Ratio**10000:1
- **Connectivity**
 - **HDMI In**1
 - **DP In**No
 - **DVI In**N/A
 - **Tuner In**N/A
 - **USB**1

- **Component In**N/A
- **Composite In**N/A
- **RGB In**N/A
- **IR In**No
- **HDBaseT In**No
- **Audio In**No
- **Audio Out**Stereo Mini Jack
- **Video Out**No
- **Power Out**N/A
- **RS232 In**Yes
- **RS232 Out**No
- **RJ45 In**Yes
- **RJ45 Out**No
- **WiFi**Yes
- **3G Dongle**No
- **Bluetooth**N/A

- **Power**
 - **Power Supply**AC100-240V 50/60Hz
 - **Power Consumption (Off Mode)**N/A
 - **Power Consumption (On Mode)**27.5
 - **Power Consumption (Sleep Mode)**0.5 W
- **Dimension**
 - **Set Dimension (WxHxD)**322 x 193.5 x 28.2 mm
 - **Package Dimension (WxHxD)**376 x 132 x 248 mm
- **Weight**
 - **Set Weight**0.9 kg
 - **Package Weight**1.7 kg
- **Operation Conditions**
 - **Temperature**0°C~ 40°C
 - **Humidity**10 ~ 80%, non-condensing
- **Mechanical Specification**
 - **VESA Mount**100 x 100 mm
 - **Bezel Width**12.2
 - **Frame Material**Non-Glossy
- **General Feature**
 - **External Memory Slot**No
- **Optional Feature**
 - **Mount**No
 - **Stand**Inbox(Simple Stand) (2ea)
- **Internal Player (MagicInfo)**
 - **MagicInfo Daisychain Videowall Support**No
- **Eco**
 - **ENERGY STAR (Latest effective version)**Yes

- **Certification and Compliance**

- **EMC** Class B FCC (USA) Part 15, Subpart B KCC/EK (Korea) Tuner : KN32 / KN35 Tunerless : KN32 / KN35 CE (Europe) EN55032 : 2012 or 2015 EN55024:2010 or EN 55035:2017 VCCI (Japan) VCCI CISPR32:2016 CCC(China) GB/T9254-2008 GB17625.1-2012 BSMI (Taiwan) CNS13438 (ITE EMI) CNS14336-1 (ITE Safety) CNS15663 (RoHS) C-Tick (Australia) AS/NZS CISPR32:2015 GOST(Russia/CIS) ROCT CISPR 24-2013 ROCT CISPR 22:2005
- **Safety** CB (Europe) : IEC60950-1/EN60950-1 CCC (China) : GB4943.1-2011 PSB (Singapore) : PSB+IEC60950-1 NOM (Mexico) : NOM-001-SCFI-1993 IRAM (Argentina) : IRAM+IEC60950-1 SASO (Saudi Arabia) : SASO+IEC60950-1 BIS (India) : IEC60950-1 / IS13252 NOM (Mexico) : Tuner : NOM-001-SCFI-1993 Tunerless : NOM-019-SCFI-1998 KC (Korea) : K 60950-1 EAC (Russia) : EAC+IEC60950-1 INMETRO (Brazil) : INMETRO+IEC60950-1 BSMI (Taiwan) : BSMI+IEC60950-1 RCM (Australia) : IEC60950-1/AS/NZS 60950-1 UL (USA) : cUL60950

