## IN114ST

# Big images for tight budgets.

The InFocus IN114ST is not only one of the lowest cost short throw projectors we've ever sold, but also has one of the longest-lasting lamps – for incredibly low total cost of ownership.

This value-packed projector is easy to buy and built to perform with high brightness, high contrast ratio and BrilliantColor<sup>™</sup> technology. Plus, the short throw lens saves space, reduces shadows, and prevents light from shining on the presenter's face.



IN114ST XGA (1024 x 768) 2500 lumens Short throw lens

#### Why choose IN114ST?

- O Ultra-low purchase price
- O Long life lamp of up to 6,000 hours lowers costs even more
- O Short throw lens for big images in tight spaces
- O High 4000:1 contrast ratio
- O Slim design and weighs only 4.8 lbs (2.17 kg)
- Accurate and vivid color reproduction with BrilliantColor technology
- 3D technology supports up to 120 Hz frame rate



Connectivity VGA x 2 Composite Video RS232 Mini USB (control & firmware)

S-Video 3.5 mm audio in 3.5 mm audio out Monitor out (VGA)

#### **Lowest Total Cost of Ownership**

The IN114ST is the lowest priced office/classroom short throw projector we've ever offered, and its lamp lasts 50% longer than the previous generation. There aren't even any filters to replace. It's an unbeatable value.

#### **High Brightness and High Contrast**

The image quality of this projector will not disappoint. 2500 lumens will give you bright, clear images with the lights on and the high 4000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface.

#### **Short Throw**

The short throw lens of the IN114ST gives you big images in tight spaces and prevents light from shining in the presenter's face. With a 0.6:1 throw ratio, you'll get a 60-inch (152 cm) wide image from only 3 feet (91 cm) away.

#### **Compact, Slim and Light**

The IN114ST is small and lightweight for easy portability from one room or building to the next. It's slim design is only 2.8 inches (70 mm) tall and weighs only 4.8 lbs (2.17 kg).



### Specifications\*

#### IN114ST

Namesolution     Vix0a120x1200       Maximum Solution     Solutansa       Ansite Solution     Solutansa <th></th> <th></th>		
Brightness     - Kormal Mode - Kor Mode     2000 lumens       Lamp Life**     - Korn Mode - Kor Mode     2000 huns       Lamp Life*     - Kormal Mode - Kor Mode     6000 huns       Contrast Rain     4000-1     - Korn Mode       Contrast Rain     4000-1     - Korn Mode       Contrast Rain     4000-1     - Korn Mode       Contrast Rain     - Korn Mode     - Korn Mode       Contrast Rain     - Korn Mode     - Korn Mode       Contrast Rain     - Korn Mode     - Korn Mode       Control     - Korn Mode     - Korn Mode       Output Sources     Montro ut (KA), Audio uto (13, mm)     - Korn Mode       Control     - Korn Mode     - Korn Mode     - Korn Mode       Control     - Korn Mode     - Korn Mode     - Korn Mode     - Korn Mode       Opelcton Offset     10%     - Korn Mode     - Korn Mode     - Korn Mode       Opelcton Offset     10%     - Korn Mode     - Korn Mode     - Korn Mode       - Korn Rain     - Korn Mode     - Korn Mode     - Korn Mode     - Korn Mode       Synch Tols Nation     <	Native Resolution	XGA 1024 x 768
- Eco Mode2000 lumesLamp Life '- Normal Mode5000 hoursContrast Ratio6000 hoursLamp Power1800 WIPContrast Ratio4000:1Contrast Ratio6 Segment , 2x SpedLinp X SourcesVGAx 2, Composite Video, 3.5 mm stereo input, RS 232C, USB B Mini (control & firmware)Output SourcesVGAx 2, Composite Video, 3.5 mm stereo input, RS 232C, USB B Mini (control & firmware)Output SourcesVGA x 2, Composite Video, 3.5 mm stereo input, RS 232C, USB B Mini for mouseAudile Noise30 dB Normal Mode (28 dB Eco Mode)Computer CompatibilityPC, MACPojector Keypad, R Renote, RS 232, USB B Mini for mouseAudile Noise30 dB Normal Mode (28 dB Eco Mode)Computer CompatibilityPC, MACNoticor ut (SA), Audio out (3, 5 mm)Computer CompatibilityPC, MACNote Control4 0º verticalLons TypeManual Zoom and focusLons TypeManual Zoom and focusLons YpeMaceNumber of Cols1.07 billionAspect Ratio50.10 HzSynch - Horizontal Scan Freq50.120 Hz-Vertical Scan Freq50.120 HzVideo Compatibility20 V(MTSC, PAL, SECAM, 4801, 5761, EU/HDV (480p, 576p, 720p, 13081, 13081, 13081, 13081, 13084 230 x 330 x 150 mm)Poduct Weight (Estimated)4.8 Ibs (3.67 kg)Nomitor ut Lins Staping Zim Kende8.108 (2.17 kg)Shipping Nimeshons (W+D>H)13.0 x 13.0 x 330 x 150 mm)Shipping Nimeshons (W+D>H)13.0 x 13.0 x 330 x 150 mm)Shipping Nimeshons	Maximum Resolution	WUXGA 1920 x 1200
Lamp Life**Normal Mode - Eco Mode5000 hoursLamp Power180W UHPContrast Ratio4000-1Color Wheel65 Segment, 2x SpeedJourboursVGA x 2, Composite Video, 5.Video, 3.5 mm stereo input, RS232C, USB B Mini (control & firmware)Output SourcesMonitor out (VGA), Audio out (3.5 mm)ControlProjector Roypad, IR Renote, RS232, USB B Mini for mouseAudible Noise30 dB Normal Mode (28 dB Eco Mode)Compute CompatibilityProjector Roypad, IR Renote, RS232, USB B Mini for mouseAudible Noise30 dB Normal Mode (28 dB Eco Mode)Compute CompatibilityProjector Roypad, IR Renote, RS232, USB B Mini for mouseAudible Noise30 dB Normal Mode (28 dB Eco Mode)Compute CompatibilityProjector Roypad, IR Renote, RS232, USB B Mini For mouseAudible Noise30 dB Normal Mode (28 dB Eco Mode)Compute CompatibilityProjector Roypad, IR Renote, RS232, USB B Mini For mouseAudible Noise30 dB Normal Adoe (28 dB Eco Mode)Compute CompatibilityProjector Roypad, IR Renote, RS44Number of Colors1.07 billionAudio0.61- Zoom Ratio1.07 billionAudio4.3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq50-120 kzVideo CompatibilitySUV (VITSC, PAL, SECAM, 4801, 5760), ED/HDIY (480p, 576p, 720p, 10801, 1080p)Audio2.0 WomoProduct Dimensions (W-D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Dimensions (W-D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Ship	Brightness - Normal Mode	2500 lumens
• Eco Mode600 hoursLamp Pover1800 HUPContrast Ratio4000.1Contrast Ratio6 Segment, 2X SpeedInput SourcesWork 2X, Composite Video, 3.5 ms stero input, RS2322, USB B Mini for mouseContral9 Soletor Keypad, R Remote, RS232, USB B Mini for mouseContral9 Soletor Keypad, R Remote, RS232, USB B Mini for mouseContral9 Soletor Keypad, R Remote, RS232, USB B Mini for mouseContral9 Soletor Keypad, R Remote, RS232, USB B Mini for mouseCompute CompatibilityPC, MACKeystone Correct4 Soletor Mando &	- Eco Mode	2000 lumens
Lamp Power     180W UP       Contrast Ratio     4000:1       Contrast Ratio     400:1       Color Wheel     6 Segmen, 2x Speed       Input Sources     WGA 2, Composite Video, 5-Video, 3.5 mm stereo input, RS232C, USB B Mini (control & firmware)       Output Sources     Monitor out (VGA), Audio out (3.5 mm)       Control     Projector (Norga), IR Remote, RS232, USB B Mini for mouse       Audible Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PC, (ACC       Projector (Norga), IR Remote, RS232, USB B Mini for mouse       Audibe Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PC, (ACC       Projection (Norga)     Remote, RS23, USB B Mini for mouse       Audio Son and focus     10%       Lens 'Throw Ratio     4.40° vertical       Lens 'Throw Ratio     0.6.1       - Zoom Ratio     1.70 bilion       Video Compatibility     0.51 10 Nitz       Video Compatibility     SD1 VINSC, PAL, SECAM, 480, S760, ED/HDIV (AB0, 576p, 720p, 1080, 1080p)       Video Compatibility     SD1 VINSC, PAL, SECAM, 480, S760, ED/HDIV (AB0, 576p, 720p, 1080, 1080p)       Video Compatibil (Estimated)     4.8 lbs (2.17 kg	Lamp Life** - Normal Mode	5000 hours
Contrast Ratio     4000:1       Color Wheel     6 Segment, 2X Speed       Input Sources     VGA X2, Composite Video, 3.5 mm stereo input, R5232C, USB B Mini (control & firmware)       Output Sources     Monitor out (VGA), Audio out (3.5 mm)       Control     Projector Keypad, IR Remote, R5232, USB B Mini for mouse       Audible Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PC, MAC       Projection Offset     40% vertical       Reystone Correction     4 0% vertical       Lons Type     Manual zoom and focus       Lons Type     0.6.61       -zoom Ratio     4.3 (Native), Supports 16:9, 16:10, Auto       Synch - Horizontal Scan Freq     31-100 kHz       - Vertical Scan Freq     31-100 kHz       - Vertical Scan Freq     50-120 Hz       Video Compatibility     SDN (NTSC, PAL, SECAM, 4801, 576), ED/HDTV (480p, 576p, 720p, 10801, 1080p)       Audio     2W mono       Product Weight (Estimated)     A.3 ta in (284 × 235 × 70 mm)       Product Weight (Estimated)     A.3 ta in (284 × 235 × 70 mm)       Product Weight (Estimated)     A.3 ta in (30 × 330 × 150 mm)       Shipping Dimensions (WxDxH)     11.5 x - 3.3 ×	- Eco Mode	6000 hours
Color Wheel     6 Segment, 2x Speed       Input Sources     VGA x2, Composite Video, S-Video, 3.5 mm stere input, RS232C, USB B Mini (control & firmware)       Output Sources     Monitor out (VGA), Audio out (3.5 mm)       Control     Projector Keypad, IR Remote, RS232, USB B Mini for mouse       Audible Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PK, MAC       Projection Offset     10%       Lens Type     Manal zoom and focus       Lens Type     Manal zoom and focus       Lens Type     Manal zoom and focus       Number of Colors     1.07 billion       Aspect Ratio     4:3 (Native), Supports 16:9, 16:10, Auto       Synch - Horizontal Scan Freq - Vertical Scan Freq -	Lamp Power	180W UHP
Input Sources     VGA x2, composite Video, S-Video, 3.5 mm stereo input, RS232C, USB B Mini (control & firmware)       Output Sources     Monitor out (VGA), Audio out (3.5 mm)       Control     Projector Keypad, IR Remote, RS232, USB B Mini for mouse       Audible Noise     30 dB Kormal Mode (28 dB Eco Mode)       Computer Compatibility     PC, MAC       Projector Offset     10%       Keystone Correction     ± 40° vertical       Lens Type     Manual zoom and focus       Lens - Throw Ratio     0.61       - Zoom Ratio     1.07 billion       Ageet Ratio     31 (10 kHz       Synch - Horizontal Scan Freq     31 (10 kHz       Synch - Horizontal Scan Freq     31 (28 k+ 235 x 70 mm)       Product Dimensions (WxD×H)     11.2 x 9.3 x 2.8 in (28 k+ 235 x 70 mm)       Product Dimensions (WxD×H)     13.0 x 3.0 x 330 x 330 x 150 mm)       Shipping Vient (Estimated)     4.8 lbs (2.17 kg)       Shipping Vient (Estimated)     3.0 4.8 m       Operating Temperature     5.0 Stor C       Security Features     Security bad, 330 x 330 x 150 mm)       Shipping Vient (Estimated)     8.1 lbs (3.6 x kg)       Shipping Vient (Estimated)     3.04 8 m <	Contrast Ratio	4000:1
Output Sources     Monitor out (VGA), Audio out (3.5 mm)       Control     Projector Keypad, IR Remote, RS 232, USB B Mini for mouse       Audible Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PC, MAC       Projection Offset     10%       Keystone Correction     ± 40° vertical       Lens Type     Manual zoon and focus       Lens Throw Ratio     0.6:1       Synch Horizontal Scan Freq     51:10.0 Auto       Synch Horizontal Scan Freq     50:12 O Hz       Video Compatibility     SDTV (NTSC, PAL, SECAM, 4801, 5761), ED/HDTV (480p, 576p, 720p, 10801, 1080p)       Audio     20 w mono       Product Weight (Estimated)     4.8 Ibs (2.17 kg)       Shipping Weight (Esti	Color Wheel	6 Segment, 2x Speed
Control     Projector Keypad, IR Remote, RS232, USB B Mini for mouse       Audible Noise     30 dB Normal Mode (28 dB Eco Mode)       Computer Compatibility     PC, MAC       Projection Offset     10%       Keystone Correction     ± 40° vertical       Lens Type     Manual zoom and focus       Lens Throw Ratio     0.6.1       -Zoom Ratio     Fixed       Number O Colors     1.07 billion       Aspect Ratio     43 (Native), Supports 16:9, 16:10, Auto       Synch - Horizontal Scan Freq     50 - 120 Hz       - Vertical Scan Freq     50 - 120 Hz       Video Compatibility     SDTV (MTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)       Audio     2 W mono       Product Dimensions (WxDxH)     11.2 x 9.3 x 2.8 in (284 x 235 x 70 mm)       Product Weight (Estimated)     4.3 (bs (2.17 kg)       Shipping Dimensions (WxDxH)     11.3 ox 4.5 p. in (33 ox 350 x 150 mm)       Shipping Weight (Estimated)     8.1 lbs (3.67 kg)       Maxium Altitude     3.048 m       Operating Temperature     5 - 35° C       Remote Control     Full Function (No laser)       Security Features     Security l	Input Sources	VGA x 2, Composite Video, S-Video, 3.5 mm stereo input, RS232C, USB B Mini (control & firmware)
Audible Noise30 dB Normal Mode (28 dB Eco Mode)Computer CompatibilityPC, MACProjection Offset10%Keystone Correction± 40° verticalLens TypeManual zoom and focusLens TypeManual zoom and focusLens - Throw Ratio0.611- Xoom RatioFixedNumber of Colors1.07 billionAspect Ratio4:3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq501 V (HTSC, PAL, SECAM, 480i, 576i), ED/HDIV (480p, 576p, 720p, 1080i, 1080p)Video CompatibilitySDIV (HTSC, PAL, SECAM, 480i, 576i), ED/HDIV (480p, 576p, 720p, 1080i, 1080p)Video Compatibility4.8 (bs (2.17 kg)Product Weight (Estimated)4.8 (bs (2.17 kg)Shipping Dimensions (Wx DxH)13.0 x 13.0 x 5.9 in (330 x 330 x 150 mm)Shipping Weight (Estimated)5.10 (kJzShipping Weight (Estimated)5.0 (kJ Scarrity bar, User PINSecurity FeaturesSocurity look (Jusc, Sarty User PINShipsing Ni-AccessoriesPower cod, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedAccessories Warranty90 adys limitedAccessories Warranty90 adys limitedAccessories Warranty90 adys limitedAccessories Warranty100 adys limitedAccessories Warranty90 adys limitedAccessories Warranty90 adys limitedAccessories Warranty90 adys limitedAccessories Warranty90 adys limitedAccessories Warranty100 adys limitedAccessorie	Output Sources	Monitor out (VGA), Audio out (3.5 mm)
Computer CompatibilityPC, MACProjection Offset10%Keystone Correction± 40° verticalLens TypeManual zoom and focusLens Type10.6:1- Zoom Ratio1.07 billionAspect Ratio4.3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq50 - 120 Hz- Vertical Scan Freq50 - 120 Hz- Vertical Scan Freq50 - 120 Hz- Video CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Weight (Estimated)4.8 Ibs (2.17 kg)Shipping Dimesions (Wx DxH)11.2 x 9.3 x 2.8 in (284 x 235 x 70 mm)Product Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty6 months limitedAccessoriesPouser Linglish, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Control	Projector Keypad, IR Remote, RS232, USB B Mini for mouse
Projection Offset     10%       Keystone Correction     ± 40° vertical       Lens Type     Manual zoom and focus       Lens Throw Ratio     6.6.1       - Zoom Ratio     Fixed       Number of Colors     1.07 billion       Aspect Ratio     4.3 (Native), Supports 16:9, 16:10, Auto       Synch - Horizontal Scan Freq     50 - 120 Hz       - Vertical Scan Freq     50 - 120 Hz       Video Compatibility     SDIV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)       Audio     2 W mono       Product Dienesions (WxD×H)     11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)       Product Weight (Estimated)     4.8 lbs (2.17 kg)       Shipping Dimensions (WxD×H)     13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)       Shipping Weight (Estimated)     8.1 lbs (3.67 kg)       Maximum Altrude     3.04 ma       Operating Temperature     5.35° C       Remote Control     Full Function (No laser)       Shipping Linectoscopies     Security lock slots, Security bar, User PIN       Ships with - Accessories     Poer cord, VGA cale, Safety instructions, User manual, Remote control       Warranty     6 months limited       <	Audible Noise	30 dB Normal Mode (28 dB Eco Mode)
Keystone Correction± 40° verticalLens TypeManual zoom and focusLens Type0.6:1- Zoom Ratio0.6:1- Zoom Ratio1.07 billionAnumber of Colors1.07 billionAspect Ratio4:3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq31 - 100 kHz- Vertical Scan Freq50 - 120 Hz- Vertical Scan Freq50 - 120 HzVideo CompatibilitySDTV (VITSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Weight (Estimated)3.048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShipsi With - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedAccessories Warranty90 days limitedMenu Languages90 days limitedManual Surguages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Funkish, Danish, Finnish, Arabic and Vietnamese)	Computer Compatibility	PC, MAC
Lens Type     Manual zoom and focus       Lens Type Katio     0.6:1       - Zoom Ratio     Fixed       Number of Colors     1.07 billion       Aspect Ratio     4:3 (Native), Supports 16:9, 16:10, Auto       Synch - Horizontal Scan Freq     50:120 Hz       - Vertical Scan Freq     50:120 Hz       Video Compatibility     SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)       Audio     2W mono       Product Dimensions (W=D×H)     1.1.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)       Product Weight (Estimated)     4.8 lbs (2.1 r kg)       Shipping Dimensions (W=D×H)     1.3.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)       Shipping Vimensions (W=D×H)     1.3.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)       Shipping Vimensions (W=D×H)     1.3.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)       Shipping Vimensions (W=D×H)     3.048 m       Operating Temperature     5.05° C       Remote Control     Full Function (No laser)       Security Fastures     Security lock slot, Security bar, User PIN       Ships With - Accessories     Power cord, VGA cable, Safety instructions, User manual, Remote control       Warranty     2 years limited       Accessor	Projection Offset	10%
LensThrow Ratio0.6:1-Zoom RatioFixedNumber of Colors1.07 billionAspect Ratio4:3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq · Vertical Scan Freq31 - 100 kHzSynch - Son Zama50 - 120 HzVideo CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (WxDxH)11.2 x 9.3 x 2.8 in (284 x 235 x 70 mm)Product Dimensions (WxDxH)13.0 x 13.0 x 5.9 in (330 x 330 x 150 mm)Shipping Dimensions (WxDxH)13.0 x 13.0 x 5.9 in (330 x 330 x 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security J ck slot, Socurity J ck slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamg Warranty6 months limitedAccessories Warranty90 days limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Keystone Correction	± 40° vertical
- Zoom RatioFixedNumber of Colors1.07 billionAspect Ratio4.3 (Native), Supports 16:9, 16:10, AutoAspect Ratio4.3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq0.12.00 kHz- Vertical Scan Freq0.12.00 kHz- Vertical Scan Freq0.12.00 kHz- Support Scan Scan Scan Scan Scan Scan Scan Scan	Lens Type	Manual zoom and focus
Number of Colors1.07 billionAspect Ratio4.3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq · Vertical Scan Freq31 - 100 kHzSort (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Video CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Vodia2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Veight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3.048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security IcaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Lens - Throw Ratio	0.6:1
Aspect Ratio4:3 (Native), Supports 16:9, 16:10, AutoSynch - Horizontal Scan Freq - Vertical Scan Freq - Vertical Scan Freq31 - 100 kHz 50 - 120 HzVideo CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Vieight (Estimated)8.1 lbs (3.67 kg)Maximun Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty90 days limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Spanish, Turkish, Danish, Finnish, Arabic and Vietnamese)	- Zoom Ratio	Fixed
Synch - Horizontal Scan Freq31 - 100 kHz- Vertical Scan Freq50 - 120 HzVideo CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Dimensions (W×D×H)3.04 % mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Number of Colors	1.07 billion
· Vertical Scan Freq50 · 120 HzVideo CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 los (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 los (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 · 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Aspect Ratio	4:3 (Native), Supports 16:9, 16:10, Auto
Video CompatibilitySDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Synch - Horizontal Scan Freq	31 - 100 kHz
Audio2 W monoProduct Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	- Vertical Scan Freq	50 - 120 Hz
Product Dimensions (W×D×H)11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Video Compatibility	SDTV (NTSC, PAL, SECAM, 480i, 576i), ED/HDTV (480p, 576p, 720p, 1080i, 1080p)
Product Weight (Estimated)4.8 lbs (2.17 kg)Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Audio	2 W mono
Shipping Dimensions (W×D×H)13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Product Dimensions (W×D×H)	11.2 × 9.3 × 2.8 in (284 × 235 × 70 mm)
Shipping Weight (Estimated)8.1 lbs (3.67 kg)Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Product Weight (Estimated)	4.8 lbs (2.17 kg)
Maximum Altitude3,048 mOperating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Shipping Dimensions (W×D×H)	13.0 × 13.0 × 5.9 in (330 × 330 × 150 mm)
Operating Temperature5 - 35° CRemote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Shipping Weight (Estimated)	8.1 lbs (3.67 kg)
Remote ControlFull Function (No laser)Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Maximum Altitude	3,048 m
Security FeaturesSecurity lock slot, Security bar, User PINShips with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Operating Temperature	5 - 35° C
Ships with - AccessoriesPower cord, VGA cable, Safety instructions, User manual, Remote controlWarranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Remote Control	Full Function (No laser)
Warranty2 years limitedLamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Security Features	Security lock slot, Security bar, User PIN
Lamp Warranty6 months limitedAccessories Warranty90 days limitedMenu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Ships with - Accessories	Power cord, VGA cable, Safety instructions, User manual, Remote control
Accessories Warranty   90 days limited     Menu Languages   19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Warranty	2 years limited
Menu Languages19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese, Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Lamp Warranty	6 months limited
Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)	Accessories Warranty	90 days limited
	Menu Languages	19 languages (English, French, German, Italian, Korean, Norwegian, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese,
		Swedish, Dutch, Polish, Turkish, Danish, Finnish, Arabic and Vietnamese)
Approvals UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe)	Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe)

\* Product specifications, terms, and offerings are subject to change at any time without notice.

\*\* Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

#### **Optional Accessories**

Replacement Lamp (SP-LAMP-069) Universal Ceiling Mount (PRJ-MNT-UNIV) LiteShow Wireless Adapter (INLITESHOW3) LiteShow Mount (PRJ-MNT-LS3) Soft Carry Case (CA-SOFTCASE-MTG) Cables and adapters Extended warranties

For more information, please visit: www.infocus.com/Accessories

#### Warranty

Providing the highest quality products and support is very important to us. The IN114ST comes standard with a 2-year limited factory warranty and 6-month limited lamp replacement warranty. Extended product and lamp warranty programs are also available.

For more information, please visit:

www.infocus.com/Support/Warranty



©2012 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. DLP, the DLP logo, and the DLP medallion are trademarks of Texas Instruments. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus\_IN14ST\_DS\_EN\_120CT12. Part Number: MMINFOCUS-0204.